

ARCHITECTURAL SPECIFICATION:

GEZE SLIMDRIVE SL

Heavy duty sliding automatic door operator

OPERATION:

The Automatic Door Operator is to be a fully electric operator, **GEZE Slimdrive SL Model** housed in an extruded aluminum low profile transom section (Height **70mm** x Width **193mm**) the unit shall comply to stringent European standards [which provides the base for AS5007-2007] and have a class 3 rating, to suit bi-parting or single sliding doors.

- The equipment will incorporate electronic computerized DC Motor with built-in optical sensor for precise movement, high torque for a maintenance free life.
- The pelmet shall incorporate an integrated and interlocking hinge for secure closure and maximum cover. The design shall enable the operator to be fitted flush to the ceiling when required, while the pelmet may be opened fully or removed for access.
- **The multifunctional microprocessor control unit shall feature the following:**
 - **Self-calibrating and programmable modes.**
 - **Fully compensates door weight and friction therefore delivering the optimum force for efficient operation.**
 - **Independent circuits for pressing closed at the end of the closing stroke.**
 - **Provision for full interfacing with all types of building security/alarm systems.**
 - **Opening speed control.**
 - **Closing speed control.**
 - **Brake control: preventing the doors from slamming shut.**
 - **End Position-damping control for accurate slow down of door movement.**
 - **Built-in UPS (uninterrupted power supply) for continued operation of door under power failure.**
 - **Automatic Cycle counting**
 - **Motor temperature monitor**
 - **Controller temperature monitor**
 - **Operating hour counter**
- The tracking system is to be dual linear track designed for accuracy and long service life fitted with no possibility of doors disengaging off tracks. The track shall be anodized for hardness and strength.
- Safety feature: Moving doors will automatically reverse when travelling if obstructed, sensitivity setting to be programmable.
- During a power failure or emergency the Failsafe device will fully open the doors. The doors will remain secure during after hours power failures but will allow emergency egress via a failsafe exit button if required. Continuous operation after power failure is optional.
- Provision for climate control shall be available. Door opening can be restricted from 50% of normal door operation during high winds or low traffic situations.
- Door drive shall be by way of toothed belt reinforced with fiberglass tensile members, will incorporate nylon facing surface for pulley tooth protection, for silent and service free *operation*.

ACTUATION:

Dual Microwave and Presence sensors - Standard
(Preferred for most applications especially where the specifier identifies elderly, infirmed, disabled or children as a likely users of the doorway]

FUNCTIONS:

Following functions are to be selectable through a wall mounted control mode switch

- **Auto - Doors are operated automatically via the movement sensors.**
- **Open - Doors maintained in open position continuously.**
- **Exit - Doors remain closed activated only by exiting traffic.**
- **Lock - Doors remain closed and locked where optional electric lock function has been installed. Exit by way of emergency exit button.**

LOCKING:

Electromechanical

An electric lock option is available to give total security and can be adapted where manual locking cannot be achieved, i.e. Frameless toughened Glass Doors. Lock type is the microprocessor controlled electric locking system. The microprocessor monitors all aspects of the locks functions; e.g. to ensure the door is fully closed when the lock is 100% engaged. Terminal outputs are available to signal to security systems both door position and lock status. The microprocessor is also self-diagnosing.

OTHER:

Maximum opening width.....	3000 mm
Maximum door weight.....	120 kg per door leaf
Opening speed double leaf, variable.....	up to 700 mm/sec
Closing speed, variable.....	50-400 mm/sec
Door open dwell time.....	0-30 sec
Manual opening/closing force.....	< 30 N

Options:

Blue tooth servers, programming & diagnostic software interface which are Ideal for concealed or difficult access applications.
Radio Remote control

INSTALLATION:

The manufacturer, window fabricator or the GEZE authorized service agent shall install the operator.

COMMISSIONING:

Operator shall be commissioned by a GEZE authorized service agent

WARRANTY:

All Geze units are covered by a 2-year parts warranty and a 12 month labour warranty, an extended warranty plan is available through an optional maintenance agreement.

PROPRIETARY ITEM: GEZE Slimdrive SL sliding door operator

Authorized Service Agent

Progressive Controls

129 Gladstone St

Fyshwick ACT 2609

PH. 6280 4655

e.sales@progressivecontrols.com.au

www.progressivecontrols.com.au



Automatic Doors & Gates
Window Control Systems
Boom Gates PVC Doors
Architectural Hardware
Sash Balances

129 Gladstone St Fyshwick ACT 2609

sales@progressivecontrols.com.au

www.progressivecontrols.com.au



Solar & Electric Gate Operators
Single/ Double Gate Kits
For Swing & Slide Gates
Automaxx Gate Operators
Australian Made & Imported



move as you like

Ph. 02 6280 4655

sungate@bigpond.net.au

www.sungateaustralia.net



Door Closers, Floor Springs
Transom Closers Panic Bars
Electric Chain Winders
Window winders
Sash Balances

Fax. 02 6280 7592

www.doorclosersonline.com.au