

Elevation Electric Window Control System

Applications

- Awning and casement windows
- High out of reach windows
- Conveniently open single or a group of windows
- Commercial buildings
- Residential buildings

Features

- Actuators can be controlled individually or grouped into zones
- Actuator can withstand 220kg applied negative pressure*
- 9kg closing force ensures a tight window seal when closed
- Smooth chain movement
- 40 seconds Opening/closing time
- 300mm chain opening
- Strong, corrosion resistant stainless steel chain (grade 304)
- Field adjustable chain limiter. Limit chain between 50-300mm @ every 10mm
- Quick clutch release Key for easy installation without power connected
- Connect and synchronize a pair of window actuators to one large window
- Ability to install actuator in multiple orientations including top and bottom chain exit.
- Will cater for window sashes as short as 300mm high**
- Can connect to touch screen display, standard wall switch or Cbus systems
- Network cabling can span up to 300m without voltage drop
- Connect and control up to 30 window actuators to a touch screen display
- Can connect multiple actuators (31 maximum) to a standard wall switch

* Through sash fixing is required to reach this force

** Please see our website for the exact window size allowance, large or short windows may be restricted in terms of opening



A PROUD AND INDEPENDENT
**100% AUSTRALIAN
OWNED COMPANY**

**Unit 3 129 Gladstone Street
Fyshwick, ACT 2609
Phone: (02) 6280 4655**